HOLT of California

CAT

The Sullair® TSR-20

Variable Speed Drive Instrument Quality Air Compressor

Rental Ready Package

- Aftercooled to 20° F above ambient final discharge air temperature.
- After-filtered to .01 PPM Oil Vapor.
- Automatic Condensate Drains.
- Auto Start and Sequencing Capability.
- Customer Hook-up (Twist Lock Connectors).
- Phase Rotation Indicator Light.
- Energy Efficient.
- 110% Environmentally Self Contained.
- Heavy Duty Rental Package
- 78 dbA @ 3'
- Efficiency Rating 96.2%
- Air Discharge Outlet Size 2"

SPECIFICATIONS

HP	100 PSI	125 PSI	150 PSI	175 PSI	START AMPS	FULL LOAD AMPS	DIMENSIONS	
100	555 CFM	485 CFM	430 CFM	380 CFM	153	153	L	13'
125	685 CFM	615 CFM	555 CFM	495 CFM	186	186	W	6'2"
150	815 CFM	740 CFM	680 CFM	610 CFM	220	220	H	7'2"
200	970 CFM	900 CFM	845 CFM	775 CFM	286	286	WT	11,600

12/02

All Amp readings based on 460 volt. All figures above are approximate.

POWERFUL SOLUTIONS

WEST SACRAMENTO
3850 Channel Drive
916-373-4155

STOCKTON
1521 W. Charter Way
209-466-6000

www.holtca.com